

ROAD

Modell	model	SQUAD 4.2 RACE tubular
Design	design	WHITE
Carbonfaser	carbon fiber	3K-Carbon
Abmaße Felge	dimension rim	tubular 28" x24,6
Reifendimension	tyres	tubular 28" 22-28mm
Reifendruck (max.)	tyre inflation pressure	15,0bar / 220psi
Bremsfläche	brake surface	XBP CARBON (patentiert / patented)
Bremsbeläge	brake pads	XeNTiS X13 Racing Shimano R55-C3 SRAM Standard BBB
Gesamtgewicht [g]	total weight [g]	1383
max. empfohlenes Fahrergewicht inkl. Ausrüstung [kg]	max. recommended rider weight incl. Equipment [kg]	110
Zubehör	accessories	XeNTiS warranty card XeNTiS wheelbag XeNTiS valve extenders for SV XeNTiS quick release

Vorderrad	front wheel	
Felgenhöhe [mm]	rim depth [mm]	42
Felgenbreite [mm]	rim width [mm]	26
Tachomagnet	speedometer magnet	✓
Vorderrad Nabe	front hub	DT SWISS 350
Einbaubreite Nabe [mm]	built in width hub [mm]	100
Speichenanzahl	spokes count	20
Speichen	spoke	Sapim CX-Ray SP
Speichennippel System	spoke-nipple system	DT Squorx
Speichenlänge [mm]	spoke lenght [mm]	271
Dekor	decor	white
Oberfläche (UV Schutz)	surface (UV protection)	shiny
empfohlene Ventillänge [mm]	recommended valve length [mm]	50
Gewicht Schnellspanner Vorderrad [g]	weight quick release front wheel [g]	44

Hinterrad	rear wheel	
Felgenhöhe [mm]	rim depth [mm]	42-ASYMMETRIC PROFILE
Felgenbreite [mm]	rim width [mm]	26
Tachomagnet	speedometer magnet	✓
Hinterrad Nabe	rear hub	DT SWISS 350
Kompatibilität 1	compatibility 1	Campagnolo 9/10/11-Speed
Kompatibilität 2	compatibility 2	Shimano 9/10/11-Speed
Kompatibilität 3	compatibility 3	SRAM 10/11-Speed
Einbaubreite Nabe	built in width hub [mm]	130
Speichenanzahl	spokes count	24
Speichen	spoke	Sapim CX-Ray SP
Speichennippel System	spoke-nipple system	DT Squorx
Speichenlänge rechts [mm]	spoke lenght right [mm]	280
Speichenlänge links [mm]	spoke lenght left [mm]	280
Dekor	decor	white
Oberfläche	surface	shiny
empfohlene Ventillänge [mm]	recommended valve length [mm]	50
Gewicht Schnellspanner Hinterrad [g]	weight quick release rear wheel [g]	49

Gewichtsschwankungen können aufgrund der Produktionsmethode des Laufrades auftreten!
Irrtümer und Änderungen vorbehalten!

Weight tolerances may occur due to the manufacturing process.
Errors and omissions excepted!