

**ROAD**

Modell	model	<b>SQUAD 5.8 RACE tubular</b>
Design	design	<b>WHITE</b>
Carbonfaser	carbon fiber	<b>3K-Carbon</b>
AbmaÙe Felge	dimension rim	<b>tubular 28" x24,6</b>
Reifendimension	tyres	<b>tubular 28" 22-28mm</b>
Reifendruck (max.)	tyre inflation pressure	<b>15,0bar / 220psi</b>
Bremsflache	brake surface	<b>XBP CARBON (patentiert / patented)</b>
Bremsbelage	brake pads	<b>XeNTiS X13 Racing Shimano R55-C3 SRAM Standard BBB</b>
Gesamtgewicht [g]	total weight [g]	<b>1383</b>
max. empfohlenes Fahrergewicht inkl. Ausrustung [kg]	max. recommended rider weight incl. Equipment [kg]	<b>110</b>
Zubehor	accessories	<b>XeNTiS warranty card XeNTiS wheelbag XeNTiS valve extenders for SV XeNTiS quick release</b>

<b>Vorderrad</b>	<b>front wheel</b>	
Felgenhohe [mm]	rim depth [mm]	<b>58</b>
Felgenbreite [mm]	rim width [mm]	<b>26</b>
Tachomagnet	speedometer magnet	<b>✓</b>
Vorderrad Nabe	front hub	<b>DT SWISS 350</b>
Einbaubreite Nabe [mm]	built in width hub [mm]	<b>100</b>
Speichenanzahl	spokes count	<b>20</b>
Speichen	spoke	<b>Sapim CX-Ray SP</b>
Speichennippel System	spoke-nipple system	<b>DT Squorx</b>
Speichenlange [mm]	spoke lenght [mm]	<b>255</b>
Dekor	decor	<b>white</b>
Oberflache (UV Schutz)	surface (UV protection)	<b>shiny</b>
empfohlene Ventillange [mm]	recommended valve length [mm]	<b>60</b>
Gewicht Schnellspanner Vorderrad [g]	weight quick release front wheel [g]	<b>44</b>

<b>Hinterrad</b>	<b>rear wheel</b>	
Felgenhohe [mm]	rim depth [mm]	<b>58-ASYMMETRIC PROFILE</b>
Felgenbreite [mm]	rim width [mm]	<b>26</b>
Tachomagnet	speedometer magnet	<b>✓</b>
Hinterrad Nabe	rear hub	<b>DT SWISS 350</b>
Kompatibilitat 1	compatibility 1	<b>Campagnolo 9/10/11-Speed</b>
Kompatibilitat 2	compatibility 2	<b>Shimano 9/10/11-Speed</b>
Kompatibilitat 3	compatibility 3	<b>SRAM 10/11-Speed</b>
Einbaubreite Nabe	built in width hub [mm]	<b>130</b>
Speichenanzahl	spokes count	<b>24</b>
Speichen	spoke	<b>Sapim CX-Ray SP</b>
Speichennippel System	spoke-nipple system	<b>DT Squorx</b>
Speichenlange rechts [mm]	spoke lenght right [mm]	<b>264</b>
Speichenlange links [mm]	spoke lenght left [mm]	<b>264</b>
Dekor	decor	<b>white</b>
Oberflache	surface	<b>shiny</b>
empfohlene Ventillange [mm]	recommended valve length [mm]	<b>60</b>
Gewicht Schnellspanner Hinterrad [g]	weight quick release rear wheel [g]	<b>49</b>

Gewichtsschwankungen konnen aufgrund der Produktionsmethode des Laufrades auftreten!  
Irrtumer und anderungen vorbehalten!

Weight tolerances may occur due to the manufacturing process.  
Errors and omissions excepted!